

AP LED-ID T H0

Suspended/Surface



Tube \varnothing 38mm



Cap \varnothing 40mm



Light output 100°



H 72mm x W 40mm

Fixing centres 470mm



Aluminium tubular diffused LED light, rear mounted integral driver.

The AP LED-ID is an aluminium extrusion, LED high output with flush fitting diffuser, can be suspended horizontally or surface mounted. The light offers a 100° light distribution through its polycarbonate opal diffuser.

Offering switched or DALI dimming options for a controllable level of light.

Suitable for almost any interior application.



AP LED-ID T HO

Suspended/Surface

Light source information

LED/Integral Electronic Driver 3000k
4000k 5000k other variants to order
please enquire.

High output.

Design

Suspended horizontally or surface
mounted.

Polycarbonate opal diffuser,
Aluminium body.

IP20.

Class II, ta 25°C 850GWT.

Dimming

Non-dimmable as standard.

DALI DSI available.

Installation

Two suspension points for fully
adjustable horizontal suspension.

Surface mounting.

Installation instructions available
on request.

Optics

Opal diffuser.

Clear diffuser available.

Photometric data available.

Miscellaneous

3hr Emergency available with extended
back box T4 and T5 only.

If you would like to change something,
please ask.

Mounting options



Suspension



AP LED-ID T HO SUSPENDED/SURFACE

PART No	WATTS w	LENGTH mm	Lm	CE	230v 50Hz
AP LED-ID T HO 2	19	595	1840	ta 25°C	Class I
AP LED-ID T HO 3	27	875	2845		
AP LED-ID T HO 4	38	1155	3465	IP20	850 GWT
AP LED-ID T HO 5	45	1435	4085		

For further information or options, call +44 (0) 1525 376974,
email reply@encapsulite.co.uk or visit www.encapsulite.co.uk