

MT70-F-IP67

Suspended/Surface

encapsulite

ILLUMINATING BY DESIGN



Tubular diffused LED light, IP67 rated.

The MT70-F-IP67 is a waterproof robust LED diffused lit tube, this can be suspended horizontally or surface mounted. The light offers a 180° distribution through its polycarbonate opal diffuser.

The MT70-F-IP67 is an incredibly versatile linear lighting solution. Black or light grey end caps from stock.

70mm diameter, (75mm \varnothing end caps) the MT70-F-IP67 makes use of efficient LED technology offering switched or DALI dimming options for a controllable level of light output.

Suitable for damp/wet areas. Not intended for permanent immersion.



MT70-F-IP67

Suspended/Surface

Light source information

LED/Electronic Driver 3000k 4000k 5000k
Other variants to order please enquire.

High efficiency, high output available see
MT70 LED T IP67.

Design

Can be suspended horizontally
or surface mounted.

Polycarbonate opal diffuser with light grey
or black end caps.

IP67 rated as standard.

Class I, ta25°C, 850GWT.

Dimming

Non-dimmable as standard.

DALI available.

Installation

Two suspension points for fully adjustable
horizontal suspension.

Surface Mounting with fixings.

Installation Instructions available on
request.

Optics

Opal diffuser.

Clear diffuser available.

Photometric data available.

Miscellaneous

3hr Emergency available Dali emergency
available.

If you would like to change something,
please ask.

Mounting options



Suspension



Plastic clamp



Stainless steel clamp

MT70-F-IP67 SUSPENDED/SURFACE

PART NR	LENGTH mm	LM/W	CIRCUIT POWER W	LUMEN	CE	230v 50-60 Hz
MT70-F1	675-705	82.5	12	965	ta 25°C	Class I
MT70-F2	1255-1285	89.4	22	1920		
MT70-F3	1840-1870	92.6	32	2974	IP67	LED
MT70-F4	2420-2450	89.4	43	3841		
MT70-F2 EC	1255-1285	-	23	276 EC	EEI A	850 GWT
MT70-F3 EC	1840-1870	-	35	276 EC		

For further information or options, call +44 (0) 1525 376974,
email reply@encapsulite.co.uk or visit www.encapsulite.co.uk