

# AP LED-RD

Suspended/Surface

encapsulite

ILLUMINATING BY DESIGN



Tube  $\varnothing$  38mm



Cap  $\varnothing$  40mm



Light output 100°

Fixing centres anywhere within 150mm each end.



## Aluminium tubular diffused LED light, remote driver.

The AP LED-RD is an aluminium extrusion, LED luminaire, remote driver up to 5m away with flush fitting diffuser, this can be suspended horizontally or surface mounted. The light offers a 100° light distribution through its polycarbonate opal diffuser.

Offering switched or DALI Dimming options for a controllable level of light.

Suitable for almost any interior application.



Asics, Oxford Street, London

# AP LED-RD

Suspended/Surface

## Light source information

LED/Remote Electronic Driver 3000k  
4000k 6000k blue, other variants to order  
please enquire.

700mA. 500mA available and will reduce  
output 25%.

## Design

Suspended horizontally or surface  
mounted.

Polycarbonate opal diffuser,  
aluminium body.

IP20.

Class II, ta 25°C 850GWT.

## Dimming

Non-dimmable as standard.

DALI or 1-10v available.

## Installation

Two suspension points for fully  
adjustable horizontal suspension.

Surface mounting.

## Optics

Opal diffuser.

Clear diffuser available.

Photometric data available.

## Miscellaneous

No emergency option.

If you would like to change something,  
please ask.

## Mounting options



Suspension




Ceiling wall



## AP LED-RD SUSPENDED/SURFACE

PART No	mA	WATTS w	LENGTH mm	DRIVER TYPE	Lm
AP-LED RD 1-700		8	315	CL700L-240-C	505
AP-LED RD 2-700		16	595	CL700-240-C	1010
AP-LED RD 3-700		24	875	CL700-240-C	1640
AP-LED RD 4-700		29	1155	CL700-240-C	2470
AP-LED RD 5-700		38	1435	CL700-240-C	2932



For further information or options, call +44 (0) 1525 376974,  
email [reply@encapsulite.co.uk](mailto:reply@encapsulite.co.uk) or visit [www.encapsulite.co.uk](http://www.encapsulite.co.uk)