

MT50 LED-T-HO AC2

Suspended/Surface

encapsulite
ILLUMINATING BY DESIGN



Tube \varnothing 50mm



Cap \varnothing 50mm



Light output 180°



Polished aluminium as standard.
Black optional.

Tubular diffused LED light, black or polished aluminium end caps.

The MT50 LED-T-HO AC2 is a slim robust LED diffused lit tubular design, this can be suspended horizontally or surface mounted. The svelte tube offers a 180° light distribution through its polycarbonate opal diffuser.

The MT50 LED-T-HO AC2 is an incredibly versatile linear lighting solution. Machined polished aluminium end caps can also be anodized black.

50mm diameter, the MT50 LED-T-HO AC2 makes use of efficient LED technology offering switched or DALI dimming options for a controllable level of light output.

Suitable for almost any interior application.



MT50 LED-T-HO AC2

Suspended/Surface

Light source information

LED/Electronic Driver 3000k 4000k 5000k other variants to order please enquire.

High efficiency and high output available.

Design

Suspended horizontally or surface mounted.

Polycarbonate opal diffuser with polished/black aluminium end caps.

IP20 rated as standard, IP67 available on request (alternative end caps).

Class I, ta 25°C, 850GWT.

Dimming

Non-dimmable as standard.

DALI DSI.

Installation

Two suspension points for fully adjustable horizontal or angled suspension.

Surface mounting with discreet fixings or clamps.

Installation Instructions available on request.

Optics

Opal diffuser.

Clear diffuser available.

Photometric data available.

Miscellaneous

3hr Emergency available HE only not HO. pre wired, Plug & Go.

If you would like to change something, please ask.

Mounting options



Suspension



Plastic clamp



Stainless steel clamp

MT50 LED-T-HO-AC2 SATIN

PART NR	LENGTH mm	SATIN Lm	CIRCUIT POWER W	LUMEN CIRCUIT W	CE	230v 50-60 Hz
MT50 LED-T2-HO AC2 SATIN	650	2415	19.0	124	ta 25°C	Class I
MT50 LED-T3-HO AC2 SATIN	950	3205	27.4	117		
MT50 LED-T4-HO AC2 SATIN	1230	4060	36.0	113	IP20	LED
MT50 LED-T5-HO AC2 SATIN	1520	5055	44.0	115		
MT50 LED-T6-HO AC2 SATIN	1810	6350	51.8	116		
MT50 LED-HE AC2 Emergency Add 40mm to T4, T5 or T6					EEL A	850 GWT

For further information or options, call +44 (0) 1525 376974,
email reply@encapsulite.co.uk or visit www.encapsulite.co.uk