## MT70-T-AC

Suspended/Surface



ILLUMINATING BY DESIGN



# Tubular diffused LED light, chrome/black aluminium end caps.

The MT70-T-AC is a flexible robust single line LED diffused lit tube design, this can be suspended horizontally or surface mounted. The cylindrical tube offers a 180° distribution of light through its polycarbonate opal diffuser.

The MT70-T-AC is an incredibly versatile linear lighting solution. Machined aluminium end caps finished in chrome or black.

70mm diameter, (75mm ø end caps) the MT70-T-AC makes use of efficient LED technology offering switched or DALI dimming options for a controllable level of light output.

Suitable for almost any interior application.



Chrome end cap standard Black optional

## MT70-T-AC

### Suspended/Surface



ILLUMINATING BY DESIGN

#### **Light source information**

LED/Electronic Driver 3000k 4000k 5000k other variants to order please enquire.

#### Design

Can be suspended horizontally or surface mounted.

Polycarbonate Opal diffuser with chrome/black aluminium end caps.

IP20 rated as standard.

#### **Dimming**

Non-dimmable as standard.

DALI DSI available.

#### Installation

Two suspension points for fully adjustable horizontal suspension.

Surface mounting with discreet fixings.

Installation Instructions available on request.

#### **Optics**

Opal diffuser.

Clear diffuser available.

Photometric data available.

#### Miscellaneous

3hr Emergency available with or without Dali monitoring. HE only, not HO

If you would like to change something, please ask.

#### **Mounting options**







Plastic clamp



SS clamp

#### MT70-T-AC SUSPENDED/SURFACE

PART NR	LENGTH mm	CLEAR Lm	Lm/CIRC W	SATIN Lm	Lm/CIRC W	CIRCUIT POWER W	CE	230v 50Hz
High efficency								
MT70-LED T2 AC	593	1015	91.44	930	83. 78	11.1	ta	
MT70-LED T3 AC	894	1635	100.93	1485	91.67	16.2	25°C	Class I
MT70-LED T4 AC	1173	2630	103.00	2230	87.45	23.7		
MT70-LED T5 AC	1463	2815	109.00	2255	87.40	25.8	IP20	LED
MT70-LED T6 AC	1755	3505	132.00	2765	104.40	26.6		
MT70-LED T4-AC EC		430 Emergency		357 Emergency		25.5	EEI	850
High output							Α	GWT
MT70-LED T2 AC-HO	593	2020	106.30	1840	102.10	19.0		
MT70-LED T3 AC-HO	894	3230	118.30	2990	109.52	27.3		
MT70-LED T4 AC-HO	1173	4345	120.70	4195	116.50	36.0		
MT70-LED T5 AC-HO	1463	5580	124.00	5220	116.00	45.0		
MT70-LED T6 AC-HO	1755	6665	128.67	6350	122.59	51.8		

Integral Emergency not available for HO version but is available for non-maintained.

For further information or options, call +44 (0) 1525 376974, email reply@encapsulite.co.uk or visit www.encapsulite.co.uk