

Bubble Wafer Horizontal 24v


Remote Driver | Suspended down-light

encapsulite

ILLUMINATING BY DESIGN



Width 60mm



Light output 110°

Thickness
Single sided
12mm



LED Bubble Diffused linear single.

The 24v LED diffused lit Wafer. The slim and robust Bubble Wafer can be suspended horizontally or angled.

The Bubble Wafer is an incredibly versatile linear lighting solution and will operate from a 24v constant voltage driver that can be DALI dimmable.



Bubble Wafer Horizontal 24v

Remote Driver | Suspended down-light

Light source information

LED/Remote Electronic Driver, 2700k, 3000k, 4000k.

Design

PMMA diffuser 650°C GWT.

Aluminium core/back.

FR4 triple row LED board.

Dimming

DALI or 1-10v available.

Installation

Suspended horizontally with powered suspension cable, or separate power cable with non powered suspension.

Optics

PMMA diffuser 650°C GWT.

Clear, semi satin or Satin.

Miscellaneous

If you would like to change something, please ask.

Mounting options



Horizontal.

BUBBLE WAFER HORIZONTAL 24V (REMOTE DRIVER)

SUSPENDED DOWN-LIGHT

PART No	WATTAGE SINGLE	LUMENS SINGLE	LENGTH mm	CIRC/W	LM/CIRC/W
BW H RD1	16w	1390lm	580	15.4	90.2
BW H RD2	28.4w	2880lm	1160	28.4	101.4
BW H RD3	42.6w	4525lm	1740	42.6	106

For further information or options, call +44 (0) 1525 376974,
email reply@encapsulite.co.uk or visit www.encapsulite.co.uk