

# MT50 LEDIAC2 INTEGRAL DRIVER



## Suspended/Surface mounted. Tubular diffused LED light, with aluminium end caps.

#### A CLASSIC LED FITTING WITH 180° OF LIGHT DISTRIBUTION.

The MT50 LED AC2 is a slim and sleek designed LED fitting. The satin or clear diffusers will enhance any space. The light can be suspended horizontally or surface mounted. The cylindrical tube offers a 180° distribution of light through its polycarbonate diffuser.

The MT50 LED AC2 is a multiple application linear lighting solution, it makes use of efficient LED technology offering switched or Dali dimming options for a controllable level of light output.

Suitable for almost any interior application.

#### **Light Source Information**

- LED/Electronic Driver.
- Available in 3000K & 4000K.

#### **Options**

- 3hr Emergency with Dali monitoring.
- Available as through wired and plug and go.
- Aluminium end caps as standard.
- Anodised end caps available in many more colours including black, rose gold and brass (see right).

### **Dimming**

Dali.

#### Installation

Horizontal, angled suspension or surface mounted.


#### **Optics**

Satin or clear polycarbonate diffuser.





Suspension Kit



Cat No.	Length (mm)	Lumens Clear	Lumens Satin	Circuit Power (W)
HIGH EFFICIENCY				
MT50 LED 2 HE AC2	607	1250	1340	12
MT50 LED 3 HE AC2	887	1950	1820	15
MT50 LED 4 HE AC2	1167	2600	2040	20
MT50 LED 5 HE AC2	1447	3410	3640	23
MT50 LED 6 HE AC2	1727	4045	3670	27
MT50 LED 7 HE AC2	2007	4700	4510	31
MT50 LED 8 HE AC2	2287	5190	5260	34
HIGH OUTPUT				
MT50 LED 2 HO AC2	607	3015	2415	19
MT50 LED 3 HO AC2	887	3690	3205	27
MT50 LED 4 HO AC2	1167	5240	4060	36
MT50 LED 5 HO AC2	1447	7165	5055	44
MT50 LED 6 HO AC2	1727	6765	8015	49
MT50 LED 7 HO AC2	2007	7920	8110	59
MT50 LED 8 HO AC2	2287	11011	9680	68



**Plastic & Stainless Steel Clamps** 



### For further information

Call: +44 (0)1525 376974 Email: reply@encapsulite.co.uk or visit www.encapsulite.co.uk