

The logo for encapsulite, featuring the brand name in a white, lowercase sans-serif font. Above the text is a decorative graphic of a series of green dots forming a curved, dotted line that suggests a light beam or a modern architectural element.

encapsulite

24V RD TWIN STICK LED

REMOTE DRIVER





Suspended/Surface mounted. Tubular diffused LED light, with aluminium end caps.

A ROBUST, SLIM LED DIFFUSED CYLINDRICAL TUBE.

The 24V RD Twin Stick is a robust, slim LED diffused cylindrical tube with the latest LED chips creating a cleaner 360° light output. The fitting can be suspended horizontally, vertically or at any angle, as well as surface mounted. Ideal as a creative feature luminaire which can incorporate many colours with the use of our coloured sleeves. Regularly used in Theatre, TV, retail, events companies, entertainment industries and for feature lighting.

The 24V RD Twin Stick will operate from a 24V constant voltage driver and can be dimmable.

Suitable for almost any dry interior application.

Light Source Information

- LED/Electronic Driver.
- Available in 2700K, 3000K & 4000K.

Options

- Aluminium end caps as standard.
- Anodised end caps available in many more colours including black, gold, rose gold and brass (see right).

Dimming

Leading/trailing edge, Dali, 1-10V.

Installation

Horizontal, vertical and angled suspension, surface mounted.

Optics

Satin polycarbonate diffuser.



Available End Cap colours



Suspension Kit & Polycarbonate clips



Discreet rear mount and side entry cable

| Cat No. | Length (mm) | Illuminated Length (mm) | Lumens | Circuit Power (W) |
|--------------|-------------|-------------------------|--------|-------------------|
| 24V RD TS 5 | 525 | 455 | 610 | 10 |
| 24V RD TS 10 | 1025 | 960 | 1380 | 19 |
| 24V RD TS 15 | 1525 | 1460 | 2015 | 27 |

Drivers available: 30W, 75W, 100W. When using 100W driver you can run the following:

| Length | Wired back to Driver | Wired end to end |
|--------|----------------------|------------------|
| 525 | X8 | X5 |
| 1025 | X5 | X4 |
| 1525 | X3 | X3 |

Total lamp wattage must not exceed driver wattage.
Max cable length from driver to light is 10m.



Tube ø 30mm



Cap ø 33mm



Light output 360°

For further information

Call: +44 (0)1525 376974

Email: reply@encapsulite.co.uk
or visit www.encapsulite.co.uk