



24V RD TWIN STICK IP64

REMOTE DRIVER





Suspended/Surface mounted. Tubular diffused light, with black IP64 end caps.

THE LATEST LED CHIPS CREATE A CLEANER LIGHT OUTPUT.

The 24V RD Twin Stick is a robust, slim LED diffused cylindrical tube with the latest LED chips creating a cleaner 360° light output. The fitting can be suspended horizontally, vertically or at any angle, as well as surface mounted. Ideal as a creative feature luminaire.

The 24V RD Twin Stick IP64 will operate from a 24V constant voltage driver and can be dimmable.

Suitable for almost any dry exterior application.

Light Source Information

- LED/Electronic Driver.
- Available in 2700K, 3000K & 4000K.

Options

- Black end caps only.

Dimming

Leading/trailing edge, Dali, 1-10V. Driver must be installed in a dry place or can be supplied in 70mm casing for external use.

Installation

Horizontal, vertical, angled suspension or surface mounted.

Optics

Satin polycarbonate diffuser.



End Cap



Suspension Kit



Polycarbonate Clips

Cat No.	Length (mm)	Illuminated Length (mm)	Lumens	Circuit Power (W)
24V RD TS WP 5	600	480	480	11
24V RD TS WP 10	1095	970	1015	19
24V RD TS WP 15	1600	1470	1450	27

Drivers available: 30W, 75W, 100W/Dali, 100W 1-10V, 60W leading/trailing edge. When using 100W driver you can run the following:



For further information

Call: +44 (0)1525 376974

Email: reply@encapsulite.co.uk

or visit www.encapsulite.co.uk



Tube ø 30mm



Cap ø 34mm



Light output 360°