

MT360 LED

REMOTE DRIVER

Code Creator



1	2	3	4
---	---	---	---

1. **Cat No.**
Please select from the table
2. **CCT – Colour Temperature**
3k
4k
3. **Cap Colour**
B – Black
W – White
4. **Wire Colour**
B – Black Cable
W – White Cable
C – Clear Cable

Fitting comes as standard with plastic mounting brackets. Stainless steel brackets and spring clips available, please advised at time of enquiry if these are required.

Suitable to be suspended horizontally or vertically with our suspension kit, please purchase separately.

Coloured sleeves available, please let us know if required.

If fitting longer than lengths listed is required, please contact us.

Drivers sold separately, please see table across for options.

If IP rated product required, please contact us.



Cat No.	Length (mm)	Illuminated Length (mm)	Lumens	Circuit Power (W)
MT360 LED V2 4	315	260	564	8
MT360 LED V2 5	385	330	729	10
MT360 LED V2 6	455	405	905	12
MT360 LED V2 7	530	475	1069	13
MT360 LED V2 8	600	545	1234	15
MT360 LED V2 9	670	620	1410	17
MT360 LED V2 10	745	690	1574	18
MT360 LED V2 11	815	760	1739	20
MT360 LED V2 12	885	835	1915	22
MT360 LED V2 13	960	905	2079	24
MT360 LED V2 14	1030	975	2245	25
MT360 LED V2 15	1100	1045	2409	28
MT360 LED V2 16	1175	1120	2585	29
MT360 LED V2 17	1245	1190	2750	31
MT360 LED V2 18	1315	1260	2914	33
MT360 LED V2 19	1390	1335	3091	35
MT360 LED V2 20	1460	1405	3255	36
MT360 LED V2 21	1530	1475	3420	38
MT360 LED V2 22	1600	1550	3596	40
MT360 LED V2 23	1675	1620	3760	42
MT360 LED V2 24	1745	1690	3925	44
MT360 LED V2 25	1815	1760	4089	45
MT360 LED V2 26	1890	1835	4266	47
MT360 LED V2 27	1960	1905	4430	49
MT360 LED V2 28	2030	1975	4594	51

W	Dimming Protocol				
	Fixed	Dali	LTE	1-10V	DMX
30	o				
100	o	o	o	o	o
150		o			

*LTE – Leading Trailing Edge
Casambi options available

For further information

Call: +44 (0)1525 376974 Email: sales@encapsulite.co.uk Visit: www.encapsulite.co.uk