

# 24V RD TWIN STICK IP64

## REMOTE DRIVER

Code Creator

1

2

**1. Cat No.**

Please select from the table

**2. CCT – Colour Temperature**

3k

4k

Fitting supplied with plastic surface mounting brackets as standard.

Fitting supplied with black caps and cable only.

Suitable to be suspended horizontally or vertically with our suspension kit, please purchase separately.

Coloured sleeves available, please let us know if required.

The fittings are available in custom lengths, should you need longer than sizes listed below please tell us at time of enquiry.

Drivers sold separately, please see table across for options.



Tube  
Ø 30mm



Cap  
Ø 34mm



Light Output  
360°



Cat No.	Length (mm)	Illuminated Length (mm)	Lumens	Circuit Power (W)
24V RD WP TS V2 4	385	240	564	8
24V RD WP TS V2 5	455	310	729	10
24V RD WP TS V2 6	530	385	905	12
24V RD WP TS V2 7	600	455	1069	13
24V RD WP TS V2 8	670	525	1234	15
24V RD WP TS V2 9	745	600	1410	17
24V RD WP TS V2 10	815	670	1574	18
24V RD WP TS V2 11	885	740	1739	20
24V RD WP TS V2 12	960	815	1915	22
24V RD WP TS V2 13	1030	885	2079	24
24V RD WP TS V2 14	1100	955	2245	25
24V RD WP TS V2 15	1170	1025	2409	28
24V RD WP TS V2 16	1245	1100	2585	29
24V RD WP TS V2 17	1315	1170	2750	31
24V RD WP TS V2 18	1385	1240	2914	33
24V RD WP TS V2 19	1460	1315	3091	35
24V RD WP TS V2 20	1530	1385	3255	36
24V RD WP TS V2 21	1600	1455	3420	38

Wattages	Dimming Protocol				
	Fixed	Dali	LTE*	1-10V	DMX
30	o				
100	o	o	o	o	o
150		o			

\*LTE – Leading / Trailing Edge

Drivers are available in 70mm Ø IP67 rated housing. If this is required, please let us know at point of enquiry

**For further information**

Call: +44 (0)1525 376974 Email: [sales@encapsulite.co.uk](mailto:sales@encapsulite.co.uk) Visit: [www.encapsulite.co.uk](http://www.encapsulite.co.uk)