



AC70 LED

REMOTE DRIVER

Code Creator

1	2	3
---	---	---

- Cat No.**
AC70 LED RD2
AC70 LED RD3
AC70 LED RD4
AC70 LED RD5

- CCT**
3k
4k

- Dimming**
F – Fixed
D – Dali
EC – Fixed with
Emergency
ECD – Dali with
Emergency

If Dali/Dali EMPRO is required, please let us know at time of enquiry

Fitting supplied with plastic surface mounting brackets as standard.

Stainless steel brackets available, please let us know at time of enquiry if these are required.

Suitable to be suspended horizontally our suspension kit, please purchase separately.

Fitting supplied with chromed silver end caps as standard, other colours available.


Please note depending on the colour requested this may influence lead time.

Please let us know at time of enquiry the colour of end caps required.


Cat No.	Length (mm)	Lumens	Circuit Power (W)
AC70 LED RD2	570	1605	16
AC70 LED RD3	955	2765	23
AC70 LED RD4	1250	36500	29
AC70 LED RD5	1545	4400	35

PHOTOMETRICS

		AC70 LED RD 2	AC70 LED RD 3	AC70 LED RD 4	AC70 LED RD 5
Photometric Measurements	Luminous Flux (lm)	1605	2765	3655	4400
	Luminous Efficacy (lm/W)	104	125	129	126
Electrical Measurements	Voltage (V)	240	240	240	240
	Current (A)	0.07	0.096	0.12	0.148
	Power (W)	15.5	22.2	28.3	34.9
	Power Factor	0.92	0.96	0.98	0.98
	Apparent Power (VA)	16.85	22.13	24.91	35.61
	Output Current DC (mA)	690	690	690	690
	Output Voltage DC (V)	17.8	26.7	36.1	44.5
	Output Power (W)	12.28	18.42	24.91	30.71
Lifetime (hrs)	Up to 50,000	Up to 50,000	Up to 50,000	Up to 50,000	



Tube
Ø 70mm



Cap
Ø 75mm



Light Output
290°



For further information

Call: +44 (0)1525 376974 Email: sales@encapsulite.co.uk Visit: www.encapsulite.co.uk