

24V RD TWIN STICK

REMOTE DRIVER

Code Creator

1	2	3	4
---	---	---	---



1. Cat No.
Please select from the table

2. CCT – Colour Temperature
3k
4k

3. Cap Colour
S – Silver (standard)
B – Black
W – White

4. Wire Colour
B – Black Cable
W – White Cable
C – Clear Cable

Fitting supplied with plastic surface mounting brackets as standard.

Slotted brackets available.

Suitable to be suspended horizontally or vertically with our suspension kit, please purchase separately.

Cable entry through end cap as standard, if rear entry cable is required, please let us know.

Coloured sleeves available, please let us know if required.

If fitting longer than lengths listed is required, please contact us.

Drivers sold separately, please see table across for options.

Cat No.	Length (mm)	Illuminated Length (mm)	Lumens	Circuit Power (W)
24V RD TS V3 6	405	345	729	9
24V RD TS V3 7	468	408	905	10
24V RD TS V3 8	530	470	1069	11
24V RD TS V3 9	593	533	1234	13
24V RD TS V3 10	655	595	1410	14
24V RD TS V3 11	718	658	1574	15
24V RD TS V3 12	780	720	1739	17
24V RD TS V3 13	843	783	1915	18
24V RD TS V3 14	905	845	2079	19
24V RD TS V3 15	968	908		21
24V RD TS V3 16	1030	970	2245	22
24V RD TS V3 17	1093	1033	2409	23
24V RD TS V3 18	1155	1095	2585	25
24V RD TS V3 19	1218	1158	2750	26
24V RD TS V3 20	1280	1220	2914	27
24V RD TS V3 21	1343	1283	3091	29
24V RD TS V3 22	1405	1345	3255	30
24V RD TS V3 23	1468	1408		31
24V RD TS V3 24	1530	1470	3420	33
24V RD TS V3 25	1593	1533	3596	34
24V RD TS V3 26	1655	1595	3760	35
24V RD TS V3 27	1718	1658	3925	37
24V RD TS V3 28	1780	1720	4089	38
24V RD TS V3 29	1843	1783	4266	39
24V RD TS V3 30	1905	1845	4430	41
24V RD TS V3 31	1968	1908		42
24V RD TS V3 32	2030	1970	4594	43



Tube
Ø 30mm



Cap
Ø 33mm



Light Output
360°



For further information

Call: +44 (0)1525 376974 Email: sales@encapsulite.co.uk Visit: www.encapsulite.co.uk