


# MT50 LED HE AC

## Technical Datasheet



**Electrical Information**

Nominal Input Voltage: 220-240V AC  
Input Frequency Range: 50-60Hz  
Surge Protection: 2kV  
Output Current: 175mA  
Dimming Protocol: Fixed / 1-10v / DALI



Concept Image

**Mechanical Information**

Mounting Type: Surface (Standard) /Suspended  
Outer Casing Material: Polycarbonate  
Diameter: 55mm

**Performance Information**

CRI: >80 (Standard) Or >90  
CCT: 3000K / 4000K / 6500K  
Macadam Step: 3  
Beam Angle: 180°  
Diffuser: Opal / Clear  
Lifetime: 72,000 Hrs


Mounting Brackets  
Plastic / Metal



**Environmental Information**

IP Rating: IP20  
Temperature Range: -20°C To +50°C  
Warranty: 3 Years

Opal



Clear



**Certification**

CE  
UKCA

Cat No.	Length (mm)	Lumens (CL) / EC	Lumens (Opal) / EC	Wattage	Weight (kg)
MT50 LED 2 HE AC	582	1552 / 769	1353 / 670	9	0.77
MT50 LED 3 HE AC	862	2328 / 751	2030 / 654	13	0.98
MT50 LED 4 HE AC	1142	3104 / 745	2712 / 649	17	1.18
MT50 LED 5 HE AC	1422	3880 / 749	3401 / 652	21	1.38
MT50 LED 6 HE AC	1702	4656 / 745	4079 / 649	26	1.58
MT50 LED 7 HE AC	1982	5432 / 748	4773 / 651	30	1.79
MT50 LED 8 HE AC	2262	6242 / 749	5452 / 652	34	2.01

All Photometric Data is measured at 4000K  
EC - Emergency Conversion  
CL - Clear Outer Casing  
Opal - Outer Casing

Encapsulite International Ltd  
Unit 17 chartmoor Road  
Chartwell business park  
Leighton buzzard, LU7 4WG

For further information or options,  
Call: 01525 376974  
Email: [sales@encapsulite.co.uk](mailto:sales@encapsulite.co.uk)  
Or visit: [www.encapsulite.co.uk](http://www.encapsulite.co.uk)