

# 24v RD TS V3

## Technical Datasheet

### Electrical Information

Nominal Input Range: 24v DC

### Mechanical Information

Mounting Type: Surface/Suspended  
Outer Casing: Polycarbonate/ABS  
Diameter: 34mm

### Performance Information

Lumen output: See Table  
CRI Rating: 95  
CCT Available: 2700K/3000K/4000K  
Macadam Step: 3  
Lifetime: Up to 50,000hrs  
Coloured Sleeves: Available

Note to be added - LED module performance Evaluated. Tp of 55°C & Ta of 25°C

### Environmental Information

IP Rating: Luminaire - IP20  
LED Driver: Remote  
Operating Temp: -20°C to +45°C  
Safety Class: II  
Power Cable: 3m (Longer Available)

### Certification

CE  
UKCA



Cat No.	Length (mm)	Illuminated Length (mm)	Lumens	Wattage
24v RD TS V3 6	405	345	564	9
24v RD TS V3 7	468	408	729	10
24v RD TS V3 8	530	470	905	11
24v RD TS V3 9	593	533	1069	13
24v RD TS V3 10	655	595	1234	14
24v RD TS V3 11	718	658	1410	15
24v RD TS V3 12	780	720	1574	17
24v RD TS V3 13	843	783	1739	18
24v RD TS V3 14	905	845	1915	19
24v RD TS V3 15	968	908	2079	21
24v RD TS V3 16	1030	970	2245	22
24v RD TS V3 17	1093	1033	2409	23
24v RD TS V3 18	1155	1095	2585	25
24v RD TS V3 19	1218	1158	2750	26
24v RD TS V3 20	1280	1220	2914	27
24v RD TS V3 21	1343	1283	3091	29
24v RD TS V3 22	1405	1345	3255	30
24v RD TS V3 23	1468	1408	TBA	31
24v RD TS V3 24	1530	1470	3420	33
24v RD TS V3 25	1593	1533	3596	34
24v RD TS V3 26	1655	1595	3760	35
24v RD TS V3 27	1718	1658	3925	37
24v RD TS V3 28	1780	1720	4089	38
24v RD TS V3 29	1843	1783	4266	39
24v RD TS V3 30	1905	1845	4430	41
24v RD TS V3 31	1968	1908	TBA	42
24v RD TS V3 32	2030	1970	4594	43

LED Driver	Fixed	DALI	1-10v	Lead/Trailing	Wireless
35w	●	●			●
60w	●	●		●	●
100w	●	●	●	●	●
150w		●		●	●
200w	●		●		
480w	●	●			