# CL360 LED V3

## Electrical Information

Nominal Input: 24v DC

## Mechanical Information

Mounting Type: Surface (Standard)
Suspended
Outer Casing: Polycarbonate/ABS
Diameter: 70mm

## Performance Information

Lumen output: See Table
CRI Rating: >90
CCT Available: 2700K/3000K/4000K
Macadam Step: 3
Lifetime: Up to 50,000hrs
Coloured Sleeves: Available

Note to be added - LED module performance Evaluated. Tp of 55°C & Ta of 25°C

## Environmental Information

IP Rating: Luminaire - IP20
LED Driver: Remote
Operating Temp: -20°C to +45°C
Safety Class: II
Power Cable: 3m (Longer Available)

## Certification

CE
UKCA



| Cat No. | Length (mm) | Lumens | Wattage | Weight (Kg) |
|---|---|---|---|---|
| CL360 LED V3 6 | 415 | 469 | 8 | 0.68 |
| CL360 LED V3 7 | 478 | 556 | 9 | 0.72 |
| CL360 LED V3 8 | 540 | 642 | 10 | 0.76 |
| CL360 LED V3 9 | 603 | 728 | 11 | 0.80 |
| CL360 LED V3 10 | 665 | 813 | 13 | 0.84 |
| CL360 LED V3 11 | 728 | 900 | 14 | 0.88 |
| CL360 LED V3 12 | 790 | 986 | 15 | 0.92 |
| CL360 LED V3 13 | 853 | 1072 | 16 | 0.96 |
| CL360 LED V3 14 | 915 | 1158 | 18 | 1.00 |
| CL360 LED V3 15 | 978 | 1245 | 19 | 1.04 |
| CL360 LED V3 16 | 1040 | 1330 | 20 | 1.08 |
| CL360 LED V3 17 | 1103 | 1417 | 22 | 1.12 |
| CL360 LED V3 18 | 1165 | 1503 | 23 | 1.16 |
| CL360 LED V3 19 | 1228 | 1589 | 24 | 1.20 |
| CL360 LED V3 20 | 1290 | 1675 | 25 | 1.24 |
| CL360 LED V3 21 | 1353 | 1762 | 27 | 1.28 |
| CL360 LED V3 22 | 1415 | 1847 | 28 | 1.32 |
| CL360 LED V3 23 | 1478 | 1934 | 29 | 1.36 |
| CL360 LED V3 24 | 1540 | 2019 | 31 | 1.40 |
| CL360 LED V3 25 | 1603 | 2106 | 32 | 1.44 |
| CL360 LED V3 26 | 1665 | 2192 | 33 | 1.48 |
| CL360 LED V3 27 | 1728 | 2279 | 34 | 1.52 |
| CL360 LED V3 28 | 1790 | 2364 | 36 | 1.56 |
| CL360 LED V3 29 | 1853 | 2451 | 37 | 1.60 |
| CL360 LED V3 30 | 1915 | 2536 | 38 | 1.64 |
| CL360 LED V3 31 | 1978 | 2623 | 40 | 1.68 |
| CL360 LED V3 32 | 2040 | 2709 | 41 | 1.72 |

## Remote Driver Options

| LED Driver | Fixed | DALI | 1-10v | Lead/ Traling Edge | Wireless |
|---|---|---|---|---|---|
| 35w | ● | ● | | | ● |
| 60w | ● | ● | | ● | ● |
| 100w | ● | ● | ● | ● | ● |
| 150w | | ● | | ● | ● |
| 200w | ● | | ● | | |
| 480w | ● | ● | | | |

Encapsulite International Ltd
Unit 17 chartmoor Road
Chartwell business park
Leighton buzzard, LU7 4WG

For further information or options,
Call: 01525 376974
Email: sales@encapsulite.co.uk
Or visit: www.encapsulite.co.uk