MTIK10 LED HO IP67

Technical Datasheet

Electrical Information

Nominal Input Voltage:	220-240V AC
Input Frequency Range:	50-60Hz
Surge Protection:	2kV
Output Current:	325mA
Dimming Protocol:	Fixed / 1-10v / DALI

Mechanical Information

Mounting Type:	Surface (Standard) /Suspended
Outer Casing Material:	Polycarbonate
Diameter:	55x57mm
Surface Brackets:	Metal Only

Performance Information

CRI:	>80 (Standard) Or >90
CCT:	3000K / 4000K / 6500K
Macadam Step:	3
Beam Angle:	180°
Diffuser:	Satin
Lifetime:	72,000 Hrs

Environmental Information

IP Rating:	IP67
IK Rating:	IK10
Temperature Range:	-20°C To +50°C
Warranty:	5Years

Certification

CE

UKCA

Concept Image





Satin

Cat No.	Length (mm)	Lumens (Satin) / EC	Wattage	Weight (kg)
MTIK10 LED 2 HO IP67	655	2512 / 670	16	1.10
MTIK10 LED 3 HO IP67	935	3769 / 648	24	1.25
MTIK10 LED 4 HO IP67	1215	5036 / 643	32	1.55
MTIK10 LED 5 HO IP67	1495	6316 / 652	40	1.85
MTIK10 LED 6 HO IP67	1775	7574 / 669	48	2.05

All Photometric Data is measured at 4000K
EC - Emergency Conversion
CL - Clear Outer Casing
Opal - Outer Casing

Encapsulite International Ltd
Unit 17 chartmoor Road
Chartwell business park
Leighton buzzard, LU7 4WG

For further information or options,
Call: 01525 376974
Email: sales@encapsulite.co.uk
Or visit: www.encapsulite.co.uk